

NIGHT VISION



MEPRO LI-OR 4X

High Performance Night Vision Sight with x4 Magnification

- › Fully compatible with 18mm ANVIS type GEN II+ or GEN III
- › Lightweight, rugged and compact configuration
- › Reticle brightness adjustment
- › Remote control cable for rapid sight activation
- › Locking mechanism for elevation and azimuth adjustment
- › MIL-STD 810



MEPRO LI-OR 4X

High Performance Night Vision Sight with x4 Magnification

NIGHT VISION



The **MEPRO LI-OR 4X** weapon sight is compact, lightweight and easy to operate. Versatile and reliable MEPRO LI-OR sight enhance sharpshooter and sniper performance in open-terrain and in urban night operations; the sight is mountable on a wide variety of weapon platforms.

The MEPRO LI-OR can be supplied with any standard high-quality 18mm image intensifier tube ensuring superior imaging quality under low-light and night conditions.

The MEPRO LI-OR magnification includes an illuminated red open-cross or mil-dot reticle. The reticle sight includes variable brightness illumination (red color) unlike most standard night vision sights, the MEPRO LI-OR reticle is visible even when reticle illumination is turned OFF or malfunctions thus providing the user with additional reliability.

Both the azimuth and elevation boresighting knobs are equipped with a safety locking mechanism.

The sight features a remote switch cable; allowing the user to rapidly turn the sight ON or OFF without removing the hands from the weapon.

The sight is powered with a single "AA" commercial battery simplifying logistics and reducing life-cycle-cost; low battery indication in field-of-view ensures the user is always aware of system's status.

Technical Specifications

Optical Data

Magnification	x4
Field of View	10.3°
Focus range	15m to infinity
Diopter adjustment	Min (+2) to (-5)
Eye relief	24mm
Reticle illuminator	5 positions
Reticle adjustment	Elevation: 0.15 mrad Windage: 0.15 mrad

Electrical Data

Battery type	1 x "AA" (Alkaline/ Lithium)
Operation time	~20 hours

Dimensions, Weight

Weight	< 1.1kg.
Dimensions LxWxH	280x76x85mm

Please Note: * Specifications are approximate and subject to change without notice ** Due to restrictions and regulations in certain countries some products may not be available for sale in your country